


SJVC系列扇形喷头



性能参数

压力 3巴 时的 喷射 角度	流量 代码	等效 喷嘴孔 径 (mm)	流量 (升/分)												喷射角度			
			0.3巴	1巴	2巴	3巴	4巴	5巴	6巴	7巴	10巴	20巴	35巴	1.5巴	3巴	6巴	14巴	
110° ~ 95° ~ 80° ~ 65° ~ 50° ~ 45° ~ 25° ~ 15°	01	0.66	0.12	0.23	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	81°	95°	105°	113°	
	015	0.79	0.19	0.34	0.48	0.59	0.68	0.76	0.84	0.90	1.1	1.5	2.0	82°	95°	105°	113°	
	02	0.91	0.25	0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	82°	95°	105°	113°	
	03	1.1	0.37	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0	83°	95°	104°	111°	
	04	1.3	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	84°	95°	103°	108°	
	05	1.4	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7	84°	95°	101°	107°	
	06	1.6	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	86°	95°	100°	106°	
	08	1.8	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	87°	95°	100°	105°	
	10	2.0	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	89°	95°	100°	105°	
	15	2.4	1.9	3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20	90°	95°	100°	100°	
	20	2.8	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	90°	95°	95°	105°	
	30	3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40	91°	95°	95°	105°	
	40	4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54	92°	95°	95°	105°	
	50	4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	93°	95°	95°	103°	
60	4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	93°	95°	95°	103°		
70	5.2	8.7	16.0	23	28	32	36	39	42	50	71	94	93°	95°	95°	103°		
0°	000067	0.58	0.08	0.15	0.22	0.26	0.31	0.34	0.37	0.40	0.48	0.68	0.90	0° 液柱流 				
	0001	0.71	0.12	0.23	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3					
	00015	0.84	0.19	0.34	0.48	0.59	0.68	0.76	0.84	0.90	1.1	1.5	2.0					
	0002	0.99	0.25	0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7					
	0003	1.2	0.37	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0					
	0004	1.4	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4					
	0005	1.5	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7					
	0006	1.7	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1					
	0008	2.0	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8					
	0010	2.2	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5					
	0015	2.7	1.9	2.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20					
	0020	3.2	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27					
	0030	3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40					
	0040	4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54					

SJVW系列扇形喷头



广角扇形流量数据表

喷嘴入口接头NPT 或BSPT (外)		流量 代码	額定噴孔 孔徑 (毫米)	流量 (升/分)										喷射角度		
				0.2巴	0.3巴	0.5巴	0.7巴	1巴	1.5巴	2巴	3巴	4巴	0.5巴	1.5巴	4巴	
1 / 8	1 / 4															
●		0.50	0.61					0.23	0.28	0.32	0.39	0.46		89°	122°	
●		0.75	0.71				0.29	0.34	0.42	0.48	0.59	0.68		106	125°	
●		1	0.84				0.38	0.46	0.56	0.64	0.79	0.91		109°	128°	
●		1.5	1.0			0.48	0.57	0.68	0.84	0.97	1.2	1.4	73°	108°	125°	
●	●	2	1.2			0.64	0.76	0.91	1.1	1.3	1.6	1.8	83°	113°	129°	
●	●	2.5	1.3		0.62	0.81	0.95	1.1	1.4	1.6	2.0	2.3	98°	122	133°	
●	●	3	1.4		0.75	0.97	1.1	1.4	1.7	1.9	2.4	2.7	86°	112°	126°	
●	●	4	1.7		1.0	1.3	1.5	1.8	2.2	2.6	3.2	3.6	97°	123°	132°	
●	●	5	1.9	1.0	1.2	1.6	1.9	2.3	2.8	3.2	3.9	4.6	114°	128°	142°	
●	●	7.5	2.3	1.5	1.9	2.4	2.9	3.4	4.2	4.8	5.9	6.8	101°	119	134°	
●	●	10	2.6	2.0	2.5	3.2	3.8	4.6	5.6	6.7	7.9	9.1	115°	133°	145°	
●	●	12	2.9	2.4	3.0	3.9	4.6	5.5	6.7	7.7	9.5	10.9	128°	139°	153°	
●	●	15	3.3	3.1	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	98°	113°	123°	
●	●	18	3.6	3.7	4.5	5.8	6.9	8.2	10.0	11.6	14.2	16.4	106°	120	131°	
●	●	20	3.8	4.1	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	110°	122°	133°	
	●	22	4.0	4.5	5.5	7.1	8.4	10.0	12.3	14.2	17.4	20	113°	125°	136°	
	●	24	4.1	4.9	6.0	7.7	9.2	10.9	13.4	15.5	18.9	22	115°	131°	144°	
	●	27	4.4	5.5	6.7	8.7	10.3	12.3	15.1	17.4	21	25	119°	135	148°	

B组件 三件组合式喷嘴